

TECHNISCHE FICHE

Bedrijf	Eurofresh NV.		
Adres	Dorpsstraat 14	Contactpersoon	Robbie Wils
Postcode & Plaats	3950 Bocholt (BE)	Telefoonnummer	003289469380

Artikelnummer	69055
Artikelbenaming	Lekvrije soeppot 280ml met transparant deksel

Dimensions	Shape:	Round	
	Volume under lid:	280ml +/- ml	The stated volume is without any head space
			The stated volume is without any head space
	External diameter top without lid:	95,8 mm	
	External diameter top with lid:	95,8 mm	
	external diameter bottom	80,3 mm	
	height without lid	60,5 +/- mm	
	height with lid	61,4 +/- mm	
	weight container	12,3 +/- g	
	standard lid	4,4 +/- g	
Closure system	Closure type:	Snap-On	
	Protective collar:	Yes	
	Tamper Evidence type:	Tamper Evidence tab	
	Lid type options:	Standard	
Handle	Handle available:	none	
Decoration	Decoration available:	IML	
	Opening used	mm	
	Overlap used	mm	
Raw material	Raw material options:	PP	
	Masterbatch colours:	Preferred colours: White 101, Clear, N	latural, Blue 201, Dark Blue 204, Black 601, Light
		Grey 502, Red 331, Yellow 430 and Gr	een 803. Additional colours: Transparent Red
			ed 307, Warm Yellow 417, Beige 421, Brown 901,
I		Dark Grey 501 (metal grey), Orange 74	41 and Blue 213. All other colours on request.
	Approvals:	All products comply with the FDA and European	
		legislation in force relating to materia	als and articles
		intended to come into contact with fo	pood.
Sturdiness	Stackability, filled:	kg (=max weight on bottom container)	
		The stacking tests have been perform	ned with the standard raw material as stated above
		•	ackability depends on many factors and the above
		•	onsequently, customers should make internal trials
		to dertermine the viability of free-sta	nding stacking and transportation. Notably,
			r than standard material, hence stacking must be
		considered when contact clear mater	ials are chosen.



TECHNISCHE FICHE

Packing	On pallet 1200x800: 9800pcs		Number Boxes on pallet: 20pcs
			Number containers per box: 490pcs
			Number lids per box: 490pcs
	Height incl. pallet:	2.25	

Performance	Hot filling:	85-95° C
		The material chosen has a very good heat resistance and the packaging is suitable for
		hot filling. Notably, plastic packaging become flexible when subjected to hot filling
		temperatures and care must be taken in relation to stacking immediately after hot filling.
		After cooling of the product and pail, the pail regains its original stacking strength.
	Cold temperatures:	The standard resin material for white/coloured products resists temperatures down to
		-20° C. Deep freezing below -20° C may require a special resin available on request.
		Standard transparent (CLX) products might become brittle at temperatures below 0° C,
		and special resins are available on request for applications below freezing. Resins
		tailored for freezing stability has a lower stackability than standard resin which must be
		taken into consideration
	Shelf life:	The compliance of the product to the technical specifications in this data sheet is
		guaranteed for 12 months after the date of the delivery subject to suitable storage.
	Quality information:	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items
		per 100,000) on a rolling 12 months basis are considered acceptable in the industry and
		therefore cannot be construed as a defect. Also, please refer to the Standard Sales and
		Delivery Terms in force at the time of delivery.

Other UN approval: No

Special: Microwave safe