



TECHNISCHE FICHE

Bedrijf	Eurofresh NV.		
Adres	Dorpsstraat 14	Contactpersoon	Robbie Wils
Postcode & Plaats	3950 Bocholt (BE)	Telefoonnummer	003289469380

Artikelnummer	69058
Artikelbenaming	Lekvrije soeppot 800ml met zwart deksel en hengsel

Dimensions	Shape:	Round	
	Volume under lid:	800ml +/- ml	The stated volume is without any head space The stated volume is without any head space
	External diameter top without lid:	131 mm	
	External diameter top with lid:	131mm	
	Height with lid	96,1 +/- mm	
	Height without lid	94,08 +/-mm	
	weight container standard lid	30g 11,5g	
Closure system	Closure type:	Snap-On	
	Protective collar:	Yes	
	Tamper Evidence type:	Tamper Evidence tab	
	Lid type options:	Standard	
Handle	Handle available:	Yes	
Decoration	Decoration available:	IML	
	Opening used	mm	
	Overlap used	mm	
Raw material	Raw material options:	PP	
	Masterbatch colours:	Preferred colours: White 101, Clear, Natural, Blue 201, Dark Blue 204, Black 601, Light Grey 502, Red 331, Yellow 430 and Green 803. Additional colours: Transparent Red 338, Silver 521, Gold 21720, Warm Red 307, Warm Yellow 417, Beige 421, Brown 901, Dark Grey 501 (metal grey), Orange 741 and Blue 213. All other colours on request.	
Approvals:	All products comply with the FDA and European legislation in force relating to materials and articles intended to come into contact with food.		 
Sturdiness	Stackability, filled:	kg (=max weight on bottom container) The stacking tests have been performed with the standard raw material as stated above at 23° C over a period of 2 months. Stackability depends on many factors and the above data is meant as an indication only. Consequently, customers should make internal trials to determine the viability of free-standing stacking and transportation. Notably, transparent (CLX) materials are softer than standard material, hence stacking must be considered when contact clear materials are chosen.	

TECHNISCHE FICHE

Packing	On pallet 1200x800: 5256pcs	Number Boxes on pallet: 24pcs
	Height incl. pallet: 2.20	Number containers per box: 219 Number lids per box: 219

Performance	Hot filling:	85-95° C The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot filling temperatures and care must be taken in relation to stacking immediately after hot filling. After cooling of the product and pail, the pail regains its original stacking strength.
	Cold temperatures:	The standard resin material for white/coloured products resists temperatures down to -20° C. Deep freezing below -20° C may require a special resin available on request. Standard transparent (CLX) products might become brittle at temperatures below 0° C, and special resins are available on request for applications below freezing. Resins tailored for freezing stability has a lower stackability than standard resin which must be taken into consideration
	Shelf life:	The compliance of the product to the technical specifications in this data sheet is guaranteed for 12 months after the date of the delivery subject to suitable storage.
	Quality information:	Deviations in the product specifications in this data sheet of 0.025% or less (i.e. 25 items per 100,000) on a rolling 12 months basis are considered acceptable in the industry and therefore cannot be construed as a defect. Also, please refer to the Standard Sales and Delivery Terms in force at the time of delivery.

Other **UN approval:** No

Special: Microwave safe